


Inbyggnadslåda

IBTronic H120TT-68-O



IBTronic H120TT-68-O

Inbyggnadslåda

Produktnummer: 97630501

Dimensioner: 306 x 150 x 151 mm

Inbyggnadslåda, for site cast or prefabricated concrete structures, for the installation of LV/HV/LED-luminaires and loudspeakers, suitable for adhesive fixing and opposing shuttering, for installation in ceilings from 180 mm, wall installation with IBT support spars, for the installation of VDE-approved lights per DIN EN 60598 (VDE 0711), as well as with F identification or MM identification, with additional connection space (e.g. for installing an electronic safety transformer up to max. 150 VA), med skyddsklass IP30, Isolationsspänning: 400V AC, halogenfri

Outlet aperture: Ø 68 mm. For the installation of VDE-tested luminaires in accordance with DIN EN 60598 (VDE 0711), and with F-identification or MM-identification, maximum installation depth LV luminaires: 120 mm, HV lights: 125 mm, lamp output halogen max. 50 W, lamp output, LED max. 20 W



Tekniska data

Elektriska egenskaper

Nominell isolationsspänning AC:	400 V
Skyddstyp:	IP30
Lämplig för:	Betongkonstruktion

Färger

Färg överdel:	övrigt
---------------	--------

Mått

Bredd:	306 mm
Längd:	150 mm
Höjd:	151 mm
Innerhöjd:	125 mm

Materialegenskaper

halogenfri:	ja
Brännbarhetsklass enligt UL94:	HB
Glödtrådstest enligt EN 60695-2-11:	650 °C
Industrikvalitet:	nej

Miljöförhållanden

max. relativ luftfuktighet 25 °C:	- %
max. relativ luftfuktighet 40 °C:	50 %
Omgivningstemperatur min.:	-25 °C
Omgivningstemperatur max.:	40 °C
Omgivningstemperatur 24h:	35 °C

Material

Material nederdel:	Polypropen
Material överdel:	Polypropen

Tillbehör

[97921801 - NAH IBTronic H 120 - Spikverktyg](#)

[97953201 - K0 K15 BL - Tomremsa](#)

[97957001 - STH 70 - Stödstag](#)

[97959001 - STH 90 - Stödstag](#)

[97960001 - STH 100 - Stödstag](#)

[97961001 - STH 110 - Stödstag](#)

[97963001 - STH 130 - Stödstag](#)

[97964001 - STH 140 - Stödstag](#)

[97965001 - STH 150 - Stödstag](#)

[97967001 - STH 170 - Stödstag](#)

[97969001 - STH 190 - Stödstag](#)

[97973001 - STH 230 - Stödstag](#)

[97974001 - STH 240 - Stödstag](#)

[97979001 - STH 290 - Stödstag](#)

Introduktion/förberedelse

$6x \leq \varnothing 34 \text{ mm}$

